


# DATA SHEET

## CROWD MICS™

### AUDIENCE ENGAGEMENT SOLUTION



Crowd Mics™ empowers audience interaction by turning smartphones into wireless microphones. Crowd Mics is comprised of two apps — one for event attendees and the other for moderators — and a small, pre-configured hardware host device, the ATOM.

The ATOM serves as the central connection point between the attendee and moderator apps and the room's AV system. It supports four audio output interfaces: 3.5mm minijack, Euroblock connector, HDMI embedded audio, and USB audio. Any combination of these outputs can be used simultaneously. Optionally, the ATOM can be connected to the room's displays via HDMI to project poll results or other event content.

The ATOM also allows moderators to see a full participation log of each event including questions asked and poll results, and can be remotely monitored and managed via SageVue™ 2.0.

Both Crowd Mics apps are supported on Apple® mobile devices running iOS® v12.0 or newer, and the attendee app is also supported on Android devices running v8.0 or newer.

Crowd Mics is perfect for the participants and moderators of presentations, lectures, panel discussions or other similar events ranging in size up to 1000 attendees.

#### BENEFITS FOR ATTENDEES

- Three ways to participate
- No waiting for a microphone
- Intuitive user interface
- Get involved without talking
- Easy-to-use polling

#### BENEFITS FOR MODERATORS

- Streamlines audience interactions
- Choose who speaks next
- Deactivate attendee mics
- Create polls and publish results
- Measure audience engagement

## CROWD MICS ATOM FEATURES

- Audio output via Euroblock, HDMI embedded audio, 3.5 minijack, or USB
- Video output via HDMI®
- Two HDMI connections for display mirroring
- Can be monitored and managed via SageVue 2.0
- CE marked, UL listed, and RoHS compliant
- Covered by Biamp Systems' two-year warranty


## ARCHITECTS & ENGINEERS SPECIFICATION

The audience engagement solution shall be comprised of a host device and two mobile applications. The first mobile application shall support event attendee functionality, including but not limited to: requesting the opportunity to talk, participating in polls conducted by the event moderator, sending text messages to the moderator, and using the built-in microphone to talk once given the opportunity by the moderator. The second mobile application shall support event moderator functionality, including but not limited to: reviewing attendees who have requested to talk, selecting an attendee to talk, creating and distributing polls, deactivating attendee microphones, and sharing poll and/or event data to an external video output. Both the attendee and moderator applications shall be supported on Apple® devices running iOS® v12.0 or newer. The attendee application shall also be supported on Android devices running v8.0 or newer. The host device shall utilize an Ethernet network via RJ-45 connector for interfacing with attendee and moderator applications, as well as for control monitoring. The host device shall be equipped with two High-Definition Multimedia Interface (HDMI®) ports, balanced analog audio outputs, and two USB 3.0 type A ports. The host device shall be CE marked, UL listed and shall be compliant with the RoHS directive. The host device warranty shall be 2 years. The audience engagement solution shall be Crowd Mics™.

## CROWD MICS ATOM SPECIFICATIONS

<b>Network Connection:</b>	Gigabit Ethernet, RJ-45 (Cat 5 and above)	<b>Power Consumption (100-240VAC 50/60Hz):</b>	< 132W
<b>Video Output:</b>		<b>Cooling:</b>	Convection
<b>Supported Resolutions:</b>	Up to 4K UHD	<b>Overall Dimensions:</b>	
<b>Physical Interface:</b>	HDMI 2.0	<b>Height:</b>	1.4 inches (35 mm)
<b>Number of Outputs:</b>	2	<b>Width:</b>	4.7 inches (120 mm)
<b>Analog Audio Output:</b>		<b>Depth:</b>	4.7 inches (120 mm)
<b>Physical Interface:</b>	Euroblock	<b>Weight:</b>	2.2 lbs (1.0 kg)
<b>Frequency Response (20Hz-20kHz, +4dBu):</b>	+0/-0.25dB	<b>Environmental:</b>	
<b>THD+N (20Hz-20kHz):</b>	< 0.006%	<b>Ambient Operating Temperature Range:</b>	32 - 95° F (0 - 35° C)
<b>Dynamic Range (20Hz-20kHz, OdB):</b>	> 96dB	<b>Humidity:</b>	0-95% relative humidity (non-condensing)
<b>Output Impedance (balanced):</b>	200Ω	<b>Altitude:</b>	0-10,000 ft (0-3000m) MSL
<b>Maximum Output:</b>	+12dBu	<b>Compliance:</b>	
<b>Sampling Rate:</b>	48 kHz		FCC Part 15B (USA)
<b>D/A Converters:</b>	24-bit		CE Marked (Europe)
<b>USB:</b>			UL and C-UL listed (USA and Canada)
<b>Version:</b>	3.0		RoHS Directive (Europe)
<b>Number of Ports:</b>	2		

## CROWD MICS ATOM REAR PANEL



Biamp, Crowd Mics, and SageVue are either trademarks or registered trademarks of Biamp Systems, LLC in the United States and other countries. HDMI, HDMI High-Definition Multimedia Interface, and the HDMI logo are either trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.